Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-304-8202

Cross Sectional Sha	pe:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating	
65.0 degrees fahren	eit and 250.0 degrees fahrenheit single response
Outside Diameter:	
0.690 inches	
Minimum Inside Ber	ding Radius:
1.000 inches	
End Application:	
3930-01-275-6420, fo	rklift truck
Connection Style:	
Swivel nut flare 2nd e	nd
End Connection De	ign:
Straight 1st end	
Connection Type:	
Threaded internal tub	e 1st end
eatures Provided:	
Reusable end fittings	
Burst Test Pressure	
20000.0 pounds per	quare inch
ayer Composition	And Location:
st layer braided cor	psion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operating	Pressure:
5000.0 pounds per so	uare inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd en	
Flow Angle:	
90.0 degrees 2nd en	
Inside Surface Cond	ition:
Smooth	
Measuring Method	Ind Length:
32.000 inches	
Media For Which De	signed:
Hydraulic fluid, and c	ease and oil, lubricating, diester base and fuel/oil, hydrocarbon and water single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0