Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-304-8250

Cross Sectio	nal Shape:
Round	
Thread Class	z de la constante de
3b 1st end	
Thread Direc	tion:
Right-hand 1s	t end
Inside Diame	ter:
0.313 inches	
Tempurature	Rating:
-65.0 degrees	fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Dian	neter:
0.469 inches	
Minimum Ins	ide Bending Radius:
4.000 inches	
Connection §	Style:
Swivel nut, fla	areless 1st end
End Connect	ion Design:
Straight 1st er	nd
Connection 1	уре:
Threaded inte	rnal tube 1st end
Features Pro	vided:
Electrostatic o	lischarge capability
Burst Test P	ressure:
9000.0 pound	s per square inch
Layer Compo	osition And Location:
Outer layer br	aided corrosion resistant steel wire
Maximum Op	erating Pressure:
1500.0 pound	s per square inch
Thread Size:	
0.562 inches	1st end
Seat Angle:	
12.0 degrees	1st end
Hydrostatic 1	Test Pressure:
3000.0 pound	s per square inch
Outer Coveri	ng Environmental Protection:
Acid resistant	and alcohol resistant and ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant
Vacuum In Te	orr:
50.8	
Inside Surfac	e Condition:
Smooth	
Measuring M	ethod And Length:

20.250 inches working

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unjf 1st end

Specification Data:

96906-ms8006 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0