## NSN 4720-01-304-8257



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-304-8257 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.334 inches **Minimum Inside Bending Radius:** 0.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided fiber and outer layer molded polyurethane **Maximum Operating Pressure:** 2500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 11.000 inches **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

## NSN 4720-01-304-8257

Nonmetallic Hose Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0