

View Online at <https://aerobasegroup.com/nsn/4720-01-304-8273>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.593 inches and 0.687 inches

Minimum Inside Bending Radius:

4.000 inches

Hose Or Tubing Specification/std Data:

Mil-h-13531, type 2 or 3, class a or b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Sae j516, table 4a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Application:

3930-01-275-6420, forklift truck

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Second End Relationship With First End:

Identical

Burst Test Pressure:

20000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided steel wire err-100 or 1st layer spirally wrapped steel fabric err-100

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches

Special Features:

Type 3 items have a layer of wire braid under the cover

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms500083 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.