NSN 4720-01-305-2099

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-2099

Crean Sastianal Shana
Cross Sectional Shape: Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
1.250 inches
End Application:
3930-01-275-6420
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and 2nd layer braided wire and outer layer braided synthetic cord
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

NSN 4720-01-305-2099

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0