Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-5801

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.490 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
2420-01-205-8636, wheeled tractor
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn and outer layer molded rubber, synthetic
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
12.0 millimeters 2nd end
Seat Angle:
60.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.875 inches
Special Features:
Metric fittings per aeroquip p/n 07.006-4-4 and 07.021-6-4
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Iso m 2nd end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0