NSN 4720-01-305-8674

Nonmetallic Hose Assembly - Page 1 of 2



Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.212 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single	gle response
Outside Diameter:	
0.410 inches	
Minimum Inside Bending Radius:	
1.500 inches	
Connection Style:	
Swivel nut, flareless 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
12.0 degrees 2nd end	
Hydrostatic Test Pressure:	
6000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Outer Covering Environmental Protection:	

Fuel resistant and solvent resistant and vibration resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

262.000 inches

Thread Series Designator:

Unjf 1st end

NSN 4720-01-305-8674

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0