NSN 4720-01-305-8676

Cross Sectional Shape:

Unf 2nd end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-8676

| Round |
|---|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.513 inches |
| Minimum Inside Bending Radius: |
| 1.000 inches |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 8000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fiber and outer layer molded polyurethane |
| Maximum Operating Pressure: |
| 2000.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 4000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 78.000 inches |
| Thread Series Designator: |

NSN 4720-01-305-8676

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0