## NSN 4720-01-305-9816

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-9816

Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.625 inches	
Minimum Inside Bending Radius:	
3.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
16000.0 pounds per square inch	
Maximum Operating Pressure:	
3000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
8000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
9.125 inches	
Media For Which Designed:	
Hydraulic fluid single response	
Thread Series Designator:	
Unjf 1st end	
Specification Data:	
96906-ms28759 government standard	

## NSN 4720-01-305-9816

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0