## NSN 4720-01-305-9818

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-9818

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:			
0.390 inches			
Minimum Inside Bending Radiu	is:		
1.500 inches			
Angle Between Rigid Elbow Fit	tings In Deg:		
0.0			
Connection Style:			
Swivel nut, flareless 2nd end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Burst Test Pressure:			
12000.0 pounds per square inch			
Layer Composition And Location	on:		
Outer layer braided corrosion res	istant steel wire		
<b>Maximum Operating Pressure:</b>			
3000.0 pounds per square inch			
Thread Size:			
0.438 inches 1st end			
Seat Angle:			
12.0 degrees 2nd end			
Hydrostatic Test Pressure:			
6000.0 pounds per square inch			
Flow Angle:			
90.0 degrees 2nd end			
Outer Covering Environmental	Protection:		
Fuel resistant and solvent resista	nt and vibration resistant		
Inside Surface Condition:			
Smooth			
Measuring Method And Length	:		
5.625 inches			

## NSN 4720-01-305-9818

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0