NSN 4720-01-305-9820

20.000 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-9820

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
0.750 inches
End Application:
3930-01-275-6420, truck, forklift
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided steel wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Heat resistant and oil resistant and ozone resistant and salt water resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

NSN 4720-01-305-9820

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0