

View Online at <https://aerobasegroup.com/nsn/4720-01-305-9822>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-50.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:

0.960 inches

Minimum Inside Bending Radius:

2.750 inches

Exterior Color:

Black

End Application:

3930-01-275-6420, fork-lift truck

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

3000.0 pounds per square inch

Layer Composition And Location:

1st layer braided fiber and 2nd layer rubber impregnated braided corrosion resistant steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

750.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

54.000 inches

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0