Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-305-9822

Cross Sectional Sh	ape:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Ratin	j:
-50.0 degrees fahrer	heit and 300.0 degrees fahrenheit single response
Outside Diameter:	
0.960 inches	
Minimum Inside Be	nding Radius:
2.750 inches	
Exterior Color:	
Black	
End Application:	
3930-01-275-6420, 1	ork-lift truck
Connection Style:	
Swivel nut flare 2nd	end
End Connection De	sign:
Straight 1st end	
Connection Type:	
Threaded internal tu	be 1st end
Features Provided:	
Reusable end fitting	3
Thready Qty Per In	ch (tpi):
12 2nd end	
Burst Test Pressur	e:
3000.0 pounds per s	quare inch
Layer Composition	And Location:
1st layer braided fibe	er and 2nd layer rubber impregnated braided corrosion resistant steel wire and outer layer molded rubber, synthetic
Maximum Operatin	g Pressure:
750.0 pounds per sc	uare inch
Thread Size:	
1.062 inches 2nd en	d
Seat Angle:	
37.0 degrees 2nd er	d
Flow Angle:	
45.0 degrees 2nd er	d
Outer Covering En	vironmental Protection:

Abrasion resistant and oil resistant

Nonmetallic Hose Assembly - Page 2 of 2

Inside Surface Condition:

Smooth

Measuring Method And Length:

54.000 inches

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

