

View Online at <https://aerobasegroup.com/nsn/4720-01-306-1016>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.312 inches

Temperature Rating:

-50.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

0.620 inches

Minimum Inside Bending Radius:

1.250 inches

Exterior Color:

Black

End Application:

Cummins eng. Kta 50

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

15000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer rubber impregnated braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

6000.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

34.000 inches

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, polyethylene

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0