Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-306-3915

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.375 inches	
Tempurature Rating:	
-40.0 degrees celsius and 149.0 degrees celsius single response	
Outside Diameter:	
0.650 inches	
Minimum Inside Bending Radius:	
2.500 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
6000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.562 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Outer Covering Environmental Protection:	
Corrosion resistant and fire resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
270.000 inches	



Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid single response

**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0