Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-306-6526

| Cross Costional Change |
|---|
| Cross Sectional Shape: Round |
| Inside Diameter: |
| 0.500 inches |
| |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: |
| 0.797 inches |
| |
| Minimum Inside Bending Radius: 5.750 inches |
| |
| Connection Style: Swivel nut flare 1st end |
| |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 24000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 6000.0 pounds per square inch |
| Seat Angle: |
| 37.0 degrees 1st end |
| Measuring Method And Length: |
| 120.000 inches excluding end fittings |
| Special Features: |
| Not for oxygen service media; tube size 0.500 in. |
| Media For Which Designed: |
| Gas single response and hydraulic fluid single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |
| |