NSN 4720-01-306-6816

Nonmetallic Tubing Assembly - Page 1 of 2



Troninctalic Tubing 7636mbly Tage Tot 2	aroup
View Online at https://aerobasegroup.com/nsn/4720-01-306-6816	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Nonmetallic Hardness Rating:	
85.0 shore durometer a	
Tempurature Rating:	
82.0 degrees celsius	
Outside Diameter:	
0.625 inches	
Exterior Color:	
Yellow, transparent	
End Application:	
4920-01-210-6697, adapter kit, depot test cell	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Identical ends	
Maximum Operating Pressure:	
13.5 pounds per square inch	
Thread Size:	
0.875 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Outer Covering Environmental Protection:	
Fuel resistant and oil resistant and solvent resistant	

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches excluding end fittings

Material:

Plastic polyurethane tube

Thread Series Designator:

Unf 1st end

NSN 4720-01-306-6816

Nonmetallic Tubing Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A541y0