Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-307-1895

Cross Sectional Shape: Round Inside Diameter: 0.688 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.062 inches Minimum Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end filtings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Cas single response and hydraulic fluid single response Sheff Life: N/a Unit Of Measure:
 Inside Diameter: 0.688 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.062 inches Minimu Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Derection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Benstring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Sheft Life: N/a Lift of Measure: To Maximum Charant Child Single response The fluid Single response and hydraulic fluid single response Sheft Life: N/a
0.688 inches Tempurature Rating: -7.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.062 inches Minimun Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seet Angle: 37.0 degrees 1st end Mesuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Messure:
Tempurature Rating: -7.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.062 inches Minimum Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Nat for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
 -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 1.062 inches Minimum Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shef Life: N/a Unit Of Measure:
Outside Diameter: 1.062 inches Minimun Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
1.062 inches Minimun Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximun Operating Pressure: 3000.0 pounds per square inch Seet Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Minimu Inside Bending Radius: 7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Saingle response and hydraulic fluid single response Sheff Life: N/a Unit Of Measure:
7.750 inches Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 1200.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Uni of Measure:
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Burst Test Pressure: 12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
12000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Maximum Operating Pressure: 3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
3000.0 pounds per square inch Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Seat Angle: 37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
37.0 degrees 1st end Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Measuring Method And Length: 88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
88.000 inches excluding end fittings Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Special Features: Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Not for oxygen service media; tube size 0.750 in. Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Media For Which Designed: Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Gas single response and hydraulic fluid single response Shelf Life: N/a Unit Of Measure:
Shelf Life: N/a Unit Of Measure:
N/a Unit Of Measure:
Unit Of Measure:
 Demilitarization:
Demilitarization:
No
Fiig:
A542a0