NSN 4720-01-309-4920

Cross Sectional Shape:

Round

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-309-4920

Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.120 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Green
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting nickel alloy all ends
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
16000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer spirally wrapped steel fabric err-100
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Inside Surface Condition:

NSN 4720-01-309-4920

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 21.000 inches Special Features: Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A542a0