## NSN 4720-01-309-6153

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-309-6153

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Rockwell corporation b1b aircraft
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
475.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
190.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
285.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant and salt water resistant
Inside Surface Condition:
Smooth

# NSN 4720-01-309-6153

Nonmetallic Hose Assembly - Page 2 of 2



### **Measuring Method And Length:**

11.500 inches working

#### **Special Features:**

Self locking nuts both ends must be approved per rockwell standard le273-0016-0006

**Thread Series Designator:** 

Unjf 1st end

### **Reference Number Differentiating Characteristics:**

As differentiated by special features

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0