NSN 4720-01-309-6155

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-309-6155
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.570 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Rockwell corporation b1b aircraft
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
475.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
190.0 pounds per square inch
Thread Size:
0.562 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

285.0 pounds per square inch

Flow Angle:

130.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant and salt water resistant

Inside Surface Condition:

Smooth

NSN 4720-01-309-6155

Fiig: A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
8.000 inches working
Special Features:
Self locking nuts both ends must meet rockwell approval per le273-0016-0006
Thread Series Designator:
Unjf 1st end
Reference Number Differentiating Characteristics:
As differentiated by special features
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No