Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-310-1755

Round Tread Class: 3b Ist and Thread Direction: Right-hand 1st and Iside Direction: 64.30 inches Tenngurture Rating: 4-0.40 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.700 inches Romotion Style: Swivel nut, flareless 2nd and Connection Design: Straight 1st and Conscion Type: Tetaded internal tube 1st end Maximum Questing Pressure: 250.0 pounds per square inch Maximum Questing Pressure: 12.0 degrees 2nd and Fired State: 0.700 inches 2nd end States 2nd and Fired State: 12.0 degrees 2nd and Grees 2nd and Fired State: 12.0 degrees 2nd and Fired State: 12.0 degrees 2nd and Fired State: 12.0 degrees 2nd and Guodegrees 2nd and Fired State: 12.0 degrees 2nd and	Rond Fixed Class: By the dit Thread Direction: Right-hand Stand Right-hand Stand Right-hand Stand Right-hand Stand Charled Stand Right-hand Stand Right-hand Stand Right-hand Stand Right-hand Stand Charled Stand Right-hand Stand Right-hand Stand Right-Barbeer Right Bibox Fittings In Deg: Right Stand Rote Right Stand Stander Stand Rote Right Stand Stander Stand Rote Rote Stander Stand Rote Stander Stand Rote Stander Stand Location: Stander Stand Location: Stander Stand Location: Stander Stand Stand Stander Stand Stander S	Cross Sectional Shape:
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.430 inches Tompurature Rating: -40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.700 inches Connection Style: Solve Inut, flareless 2nd end End Connection Design: Straight 1st end Composition And Location: Ital ave traiked corrosion resistant steel wire and 2nd layer braiked polyamide cord and outer layer molded rubber, chloropreter Maximum Operating Pressure: 20.0 pounds per square inch Triced Size 10.1 Confere Condition: 11.2 Confere Condition: 12.0 degrees 2nd end Flow Angle: 12.0 degrees 2nd end Flow Angle: 12.0 degrees 2nd end Inside Urace Condition: Smooth Messuring Method And Length: 20.00 inches working	3b Isl and Tread Direction: Righ-hand 1st end Righ-hand 1st end Inside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 4-00 degrees fahrenheit and 16.00 degrees fahrenheit single response Outside Diameter: 90.0 Connection Design: Stard Internation Design: Stard Internation Design: Stard Internation Design: Stard Internation Design: 12 degrees 2nd end Stard Angle: 12.00 degrees 2nd end Stard Angle: 12.00 degrees 2nd end Stard Angle: 12.00 degrees 2nd end	
Tread Direction: Right-hand 1st end Inside Diameter: 0.430 inches Temprature Rating: 4.00 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.700 inches Poncetion Style: Swivel nut, flareless 2nd end End Connection Design: Stright 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropter Mixman Operating Pressure: 25.00 pounds per square inch Thread Size: 0.750 inches 2nd end Start Angle: 12.0 degrees 2nd end Enderdiant: 0.760 degrees 2nd end Size Angle: 12.0 degrees 2nd end Size Angle: <tr< td=""><td>Tread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0.430 inches Tempurature Rating: 4.00. degrees fahrenheit and 160.0 degrees fahrenheit single response Ottide Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.700 inches Onnection Style: Solo Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Solo Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Solo pourds per square inch Straight 1st end Connection Type: Thread Straige Pressure: Solo pourds per square inch Ruiter Solo degrees 2nd end Flow Angle: 0.10 degrees 2nd end Flow Angle: 0.20 degrees 2nd end Straiget Strate Condition: Strate Strate Condition: Strate Strate Strate Strate S</td><td>Thread Class:</td></tr<>	Tread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 0.430 inches Tempurature Rating: 4.00. degrees fahrenheit and 160.0 degrees fahrenheit single response Ottide Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.700 inches Onnection Style: Solo Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Solo Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Solo pourds per square inch Straight 1st end Connection Type: Thread Straige Pressure: Solo pourds per square inch Ruiter Solo degrees 2nd end Flow Angle: 0.10 degrees 2nd end Flow Angle: 0.20 degrees 2nd end Straiget Strate Condition: Strate Strate Condition: Strate Strate Strate Strate S	Thread Class:
Right-hand 1st end Inside Diameter: 0.430 inches Tempurature Rating: -40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swiel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroptere Maximu Operating Pressure: 25.0 pounds per square inch Thread Size: 0.750 inches 2nd end Stat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Contion: Smooth Measuring Method And Length: 20.00 inches working	Right-hand 1st end Inside Diameter: 0.430 inches Tempurature Raing: 40.0 degrees Ainerhein: and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigd Elbow Fittings In Deg: 0.000 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Straight 1st end Sol.0 Sol.0 Presente: Sol.0 Sol.0 Straight 1st end Layer Composition And Location: Straight Straight 1st end Layer Composition And Location: Sol.0 pounds per square inch Thread Size: 0.750 inches 2nd end Flow Angle: 12.0 degrees 2nd end Resuring Method And Length: 2.0.0 inches working Thread Size: 2.0.0 inches working Thread Size: 2.0.0 inches working Th	3b 1st end
Inside Diameter: 0.430 inches Tempurature Rating: -40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 0.00 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprere Maximu Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Straight 300 Straight 300 Straight 300 Straight 300 Outgrees 2nd end Flow Angle: 12.0 degrees 2nd end Straight 300 Straight 300 <t< td=""><td>n- indie Diameter: 0.430 inches Temputative Rating: 4.00 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.00 inches 7.00 in</td><td>Thread Direction:</td></t<>	n- indie Diameter: 0.430 inches Temputative Rating: 4.00 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.00 inches 7.00 in	Thread Direction:
0.430 inches Tempurature Rating: -40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Ornotetion Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropter Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.700 inches 2nd end Else Angle: 12.0 degrees 2nd end Flow Angle: 0.0 degrees 2nd end Ensolution: Smoth Masseried Condition: Smoth Messuring Method And Lengtin: 2000 inches working	0.430 inches Tempurature Rating: 40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Right Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 20.0 pounds per square inch Thread Size: 0.700 inches 2nd end Flow Angle: 2.0.0 degrees 2nd end Flow Angle: 2.0.0 degrees 2nd end Messuring Method And Length: 2.0.00 inches working Thread Size 2.0.01 inches working <td>Right-hand 1st end</td>	Right-hand 1st end
Tempurature Rating: 40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Ornoction Type: Threaded internal tube 1st end Layer Domosition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprent Maximum Operating Pressure: 260.0 pounds per square inch Thread Size: 0.700 inches 2nd end End Congeres 2nd end Straight 200 pounds per square inch Thread Size: 0.700 inches 2nd end Bougrees 2nd end Flow Angle: 0.700 inches 2nd end Isole Surface Condition: Smoth Smoth Surface Condition: Smoth Surface Condition: Smoth Laide Surface Condition: Smoth Messering Method And Length: 2000 inches working	Tempurature Rating: 40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigd Elbow Fittings In Deg: 0.00 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: Straight Pressure: 250.0 pounds per square inch Thread Stale 0.700 inches 2nd end Straight St end 12.0 degrees 2nd end Straight St end 12.0 degrees 2nd end File 12.0 degrees 2nd end Straight St end 12.0 degrees 2nd end File 12.0 degrees 2nd end Straight St end Straige 12.0 degrees 2nd end File 12.0 degrees 2nd end Straight St end Straige 12.0 degrees 2nd end File 12.0 degrees 2nd end Straight St end Straige	Inside Diameter:
40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprer Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Fiov Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flateless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: Na	0.430 inches
Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroperer Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Surdace Condition: Smooth Master Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Outside Diameter: 0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Inside Surface Condition: Smooth Massuring Method And Length: 32.000 inches working Thread Series Designator: Unjt 1st end Shell Life: Nao Nat	Tempurature Rating:
0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	0.700 inches Angle Between Rigid Elbow Fittings In Deg: 90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 25.0.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 10.760 inches 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 20.000 inches working Thread Series Designator: Unif 1st end Shef Life: Na	-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Angle Between Rigid Elbow Fittings In Deg: 30.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Masde Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Angle Between Rigid Elbow Fittings in Deg: a0.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Istide Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Ling fi 1st end Shoff Life: Na Via	Outside Diameter:
a.o. Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroperer Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smoth Measuring Method And Length: 32.000 inches working Thread Series Designator:	90.0 Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Steat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Size: Unjf 1st end Sheft Life: Na Unit Of Measure:	0.700 inches
Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Connection Style: Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Steat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smoth Measuring Method And Length: 32.000 inches working Thread Steis Designator: Unjf 1st end Sheft Life: Na	Angle Between Rigid Elbow Fittings In Deg:
Swivel nut, flareless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Steise Designator:	Swivel nut, flaveless 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 22.000 inches working Thread Series Designator: Unjf 1st end Sheft Life: Na	90.0
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 250.0 pounds per square inch 250.0	Connection Style:
Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Straight 1st end Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Sheff Life: N/a Unit Of Measure: 	Swivel nut, flareless 2nd end
Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Connection Type: Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: Na Unif Of Measure:	End Connection Design:
Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working	Threaded internal tube 1st end Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Straight 1st end
Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Layer Composition And Location: 1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:	Connection Type:
1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloropren Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:	Threaded internal tube 1st end
Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working	Maximum Operating Pressure: 250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:	Layer Composition And Location:
250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	1st layer braided corrosion resistant steel wire and 2nd layer braided polyamide cord and outer layer molded rubber, chloroprene
Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Thread Size: 0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Maximum Operating Pressure:
0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	0.750 inches 2nd end Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: N/a	250.0 pounds per square inch
Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Seat Angle: 12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure:	Thread Size:
12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	12.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	0.750 inches 2nd end
Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Flow Angle: 90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Seat Angle:
90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	90.0 degrees 2nd end Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	12.0 degrees 2nd end
Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Inside Surface Condition: Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Flow Angle:
Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator:	Smooth Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	90.0 degrees 2nd end
Measuring Method And Length: 32.000 inches working Thread Series Designator:	Measuring Method And Length: 32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Inside Surface Condition:
32.000 inches working Thread Series Designator:	32.000 inches working Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure:	Smooth
Thread Series Designator:	Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: 	Measuring Method And Length:
	Unjf 1st end Shelf Life: N/a Unit Of Measure:	32.000 inches working
Linif 1st end	Shelf Life: N/a Unit Of Measure:	Thread Series Designator:
	N/a Unit Of Measure: 	Unjf 1st end
Shelf Life:	Unit Of Measure:	Shelf Life:
N/a		N/a
Unit Of Measure:		Unit Of Measure:

No

NSN 4720-01-310-1755

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

