NSN 4720-01-311-0982

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

0.212 inches

Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-311-0982

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:
0.400 inches
Minimum Inside Bending Radius:
1.500 inches
Angle Between Rigid Elbow Fittings In Deg:
260.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Fuel resistant and vibration resistant and heat resistant and solvent resistant
Inside Surface Condition:
Smooth

NSN 4720-01-311-0982

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
8.500 inches working
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A542a0