NSN 4720-01-311-0983



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-311-0983 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.498 inches **Minimum Inside Bending Radius:** 2.750 inches **Exterior Color:** Black **Connection Style:** Swivel, plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and outer layer molded polyurethane **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.250 inches 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 65.000 inches **Special Features:** Permanently attached fittings **Thread Series Designator:** Npt 1st end

Shelf Life:

N/a

NSN 4720-01-311-0983

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0