NSN 4720-01-311-0984



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-311-0984 **Cross Sectional Shape:** Round **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.498 inches **Minimum Inside Bending Radius:** 2.750 inches **Exterior Color:** Black **Connection Style:** Swivel, plain 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Features Provided:** Perforated outer cover **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided synthetic cord and outer layer molded polyurethane **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.250 inches 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:**

30.000 inches

Special Features:

Permanently attached fittings

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

NSN 4720-01-311-0984

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0