

View Online at <https://aerobasegroup.com/nsn/4720-01-312-1003>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

5.000 inches

**End Application:**

Anch or gate valve

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Nonskive

**Burst Test Pressure:**

16000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

4000.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.000 inches excluding end fittings

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0