## NSN 4720-01-312-1008

Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-312-1008

Cross Sectional Shape:			
Round			
Thread Class:			
2b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
1.000 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
1.500 inches			
Minimum Inside Bending Radius:			
12.000 inches			
Connection Style:			
Swivel nut flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Nonskive and perforated outer cover			
Thready Qty Per Inch (tpi):			
12 1st end			
Burst Test Pressure:			
8000.0 pounds per square inch			
Layer Composition And Location:			
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic			
Maximum Operating Pressure:			
2550.0 pounds per square inch			
Thread Size:			
1.312 inches 1st end			
Seat Angle:			
37.0 degrees 1st end			
Outer Covering Environmental Protection:			
Abrasion resistant and oil resistant and weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
21.640 inches			
Media For Which Designed:			

## NSN 4720-01-312-1008

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	ator:

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0