NSN 4720-01-312-1879

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-312-1879

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant and ozone resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.406 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-312-1879

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
81343-j517 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0