Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-312-5050

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 125.0 degrees fahrenheit single response	
Outside Diameter:	
0.500 inches	
Minimum Inside Bending Radius:	
4.000 inches	
End Application:	
Aircraft, galaxy, c-5	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Perforated outer cover	
Burst Test Pressure:	
26100.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided steel wire and outer layer molded polyurethane	
Maximum Operating Pressure:	
6530.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
13160.0 pounds per square inch	
Criticality Code Justification:	
Feat	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
10.000 inches	



## **Special Features:**

Weapon system essential

## Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

A542a0