

View Online at <https://aerobasegroup.com/nsn/4720-01-312-9598>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.750 inches

Minimum Inside Bending Radius:

1.750 inches

End Application:

CATE-RP-ILL-ARIN

Connection Style:

Inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Features Provided:

Perforated outer cover

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided cotton cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

400.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

119.000 inches

Media For Which Designed:

Brake fluid, nonmineral oil single response

Thread Series Designator:

Ptf-sae short 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0