

View Online at <https://aerobasegroup.com/nsn/4720-01-314-1034>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.342 inches

**Temperature Rating:**

-450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response

**Outside Diameter:**

0.603 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Inner Conveying Tube Style:**

Annular open-pitch corrugated

**Angle Between Rigid Elbow Fittings In Deg:**

150.0

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Identical ends

**Burst Test Pressure:**

7600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Thread Size:**

0.562 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Measuring Method And Length:**

10.000 inches working

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0