

View Online at <https://aerobasegroup.com/nsn/4720-01-314-1034>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.342 inches

Temperature Rating:

-450.0 degrees fahrenheit single response and 1200.0 degrees fahrenheit single response

Outside Diameter:

0.603 inches

Minimum Inside Bending Radius:

4.000 inches

Inner Conveying Tube Style:

Annular open-pitch corrugated

Angle Between Rigid Elbow Fittings In Deg:

150.0

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Identical ends

Burst Test Pressure:

7600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Measuring Method And Length:

10.000 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0