## NSN 4720-01-314-2116

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-314-2116

Cross Sectional Shape
Cross Sectional Shape: Round
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response  Outside Diameter:
0.945 inches
Minimum Inside Bending Radius: 5.500 inches
Hose Or Tubing Specification/std Data:
Sae j517, 100r5; type a-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).
End Application:
HARN-IS-CHF-EGER
Features Provided:
Reusable end fittings
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:
1750.0 pounds per square inch
Hydrostatic Test Pressure:
3500.0 pounds per square inch  Inside Surface Condition:
Smooth
Measuring Method And Length:
351.000 inches working
Special Features:
Used on outrigger hydraulic assembly
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Specification Data:  See iE17 100rE; type a 81212 petianal atd/ana.
Sae j517, 100r5; type a-81343 national std/spec
Shelf Life:
N/a Unit Of Measure:
Unit of Measure:
Demilitarization:
No Eila:
Fiig: A542a0
A542a0