

View Online at <https://aerobasegroup.com/nsn/4720-01-314-2123>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Tempurature Rating:

-32.0 degrees celsius single response and 52.0 degrees celsius single response

Outside Diameter:

2.125 inches

Hose Or Tubing Specification/std Data:

Mil-h-370, size 5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil-c-27487 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

1.500 inches 1st end

Connection Style:

Cam or lever (external) 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting copper alloy all ends

Connection Type:

External quick disconnect 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord err-100

Hydrostatic Test Pressure:

150.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches

Specification Data:

81349-mil-h-370f government specification

Specification Or Standard:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-c-27487 spec.