

View Online at <https://aerobasegroup.com/nsn/4720-01-314-2522>

Cross Sectional Shape:

Round

Thread Class:

3b 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

1.688 inches

Minimum Inside Bending Radius:

4.500 inches

End Application:

1520-01-125-5547

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thread Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

400.0 pounds per square inch

Layer Composition And Location:

1st layer braided polyester cord and outer layer braided polyester cord

Maximum Operating Pressure:

100.0 pounds per square inch

Thread Size:

1.065 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

200.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0