NSN 4720-01-314-2522



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-314-2522 **Cross Sectional Shape:** Round **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.750 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 1.688 inches **Minimum Inside Bending Radius:** 4.500 inches **End Application:** 1520-01-125-5547 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 400.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyester cord and outer layer braided polyester cord **Maximum Operating Pressure:** 100.0 pounds per square inch **Thread Size:** 1.065 inches 2nd end Seat Angle: 37.0 degrees 2nd end **Hydrostatic Test Pressure:** 200.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches

NSN 4720-01-314-2522

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0