Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-314-3499

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.406 inches

Tempurature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.562 inches

Minimum Inside Bending Radius:

4.625 inches

Exterior Color:

Natural

Quick Disconnect Size:

0.750 inches 2nd end

Connection Style:

Push (internal) 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Internal quick disconnect 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Seat Angle:

37.0 degrees 2nd end

Inside Surface Condition:

Smooth

Special Features:

W/90 degrees flow elbow, both ends and coupling half, quick disconnect

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 4720-01-314-3499

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

