Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-315-5892

view Online at https://aerobasegroup.com/nsi//4720-01-315-5692
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.360 inches and 0.390 inches
Minimum Inside Bending Radius:
1.500 inches
Angle Between Rigid Elbow Fittings In Deg:
260.0
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Fuel resistant and vibration resistant and heat resistant and solvent resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

10.750 inches working

NSN 4720-01-315-5892

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as120 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0