Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-316-1073

| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.750 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.945 inches |
| Minimum Inside Bending Radius: |
| 2.750 inches |
| Connection Style: |
| Straight 1st end |
| Connection Type: |
| Unthreaded external hose 1st end |
| Burst Test Pressure: |
| 75.0 pounds per square inch |
| Maximum Operating Pressure: |
| 34.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 50.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 10.875 inches |
| Inside Diameter Hose Accommodated: |
| 0.750 inches 1st end |
| Special Features: |
| Includes cres spring and reinforced green nomex cover; fiberglass reinforced sleeve included |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |
| |
| |