## NSN 4720-01-317-4434

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-317-4434

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.750 inches   |
| Tempurature Rating:  |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                                |
| Outside Diameter:  |
| 1.100 inches   |
| Minimum Inside Bending Radius:   |
| 6.000 inches   |
| Exterior Color:  |
| Black  |
| End Application:   |
| Truck forklift model w106y   |
| Connection Style:  |
| Swivel nut flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 12 1st end   |
| Burst Test Pressure:   |
| 9000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, nitrile |
| Maximum Operating Pressure:  |
| 2250.0 pounds per square inch  |
| Thread Size:   |
| 1.062 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Hydrostatic Test Pressure:   |
| 4500.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Abrasion resistant and oil resistant and weatherproof  |

Smooth

**Inside Surface Condition:** 

## NSN 4720-01-317-4434

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Length: |
|------------------------------|
| 36.000 inches                |
| Thread Series Designator:    |
| Un 1st end                   |
| Shelf Life:                  |
| N/a                          |
| Unit Of Measure:             |
|                              |
| Demilitarization:            |
| No                           |

**Fiig:** A542a0