## NSN 4720-01-317-8923

**Cross Sectional Shape:** 

Round

Unjs 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-317-8923

Thread Class:			
3b 1st end			
Thread Direction:			
Right-hand 1st end			
Inside Diameter:			
0.212 inches			
Tempurature Rating:			
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response			
Outside Diameter:			
0.470 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Connection Style:			
Swivel nut, inverted flare 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded internal tube 1st end			
Features Provided:			
Nuts drilled for lockwire			
Thready Qty Per Inch (tpi):			
20 1st end			
Burst Test Pressure:			
16000.0 pounds per square inch			
Layer Composition And Location:			
Outer layer braided corrosion resistant steel wire			
Maximum Operating Pressure:			
4000.0 pounds per square inch			
Thread Size:			
0.562 inches 1st end			
Seat Angle:			
8.5 degrees 1st end			
Hydrostatic Test Pressure:			
8000.0 pounds per square inch			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
94.000 inches			
Thread Series Designator:			

## NSN 4720-01-317-8923

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

1w025-07a287 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0