NSN 4720-01-317-8929

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-317-8929

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.375 inches				
Tempurature Rating:				
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response				
Outside Diameter:				
0.688 inches				
Minimum Inside Bending Radius:				
5.000 inches				
End Application:				
Wiggins lift co forklift model w106y				
Connection Style:				
Swivel nut flare 2nd end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
9000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene				
Maximum Operating Pressure:				
2250.0 pounds per square inch				
Thread Size:				
0.562 inches 2nd end				
Seat Angle:				
37.0 degrees 2nd end				
Hydrostatic Test Pressure:				
4500.0 pounds per square inch				
Flow Angle:				
90.0 degrees 2nd end				
Outer Covering Environmental Protection:				
Oil resistant and ozone resistant and weatherproof				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				

24.000 inches

NSN 4720-01-317-8929

Nonmetallic Hose Assembly - Page 2 of 2



-	laa a al	C!	D!	_4
ı	nread	Series	Design	ator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0