Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-317-8933

Cross Sectional Shape:
Round
Thread Class:

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.780 inches

Minimum Inside Bending Radius:

3.500 inches

Exterior Color:

Black

End Application:

Truck forklift model w106y

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber, nitrile

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

54.000 inches

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0