NSN 4720-01-318-3596

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-318-3596

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.665 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
1.253 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.500 inches
Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-01-318-3596

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0