NSN 4720-01-320-5334

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-320-5334 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.190 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.520 inches **Minimum Inside Bending Radius:** 1.500 inches **End Application:** 4320-01-284-1065, centrifical pump unit **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1750.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated woven fabric **Maximum Operating Pressure:** 350.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.000 inches and 12.500 inches **Special Features:**

Hose used for propane

Media For Which Designed:

Butane single response

Thread Series Designator:

Unf 1st end

NSN 4720-01-320-5334

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0