NSN 4720-01-321-2557

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-321-2557

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches Connection Style:							
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Thread Direction: Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Right-hand 1st end Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Inside Diameter: 0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
0.500 inches Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Tempurature Rating: 200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
200.0 degrees fahrenheit single response Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Outside Diameter: 0.880 inches Minimum Inside Bending Radius: 5.000 inches							
0.880 inches Minimum Inside Bending Radius: 5.000 inches							
Minimum Inside Bending Radius: 5.000 inches							
5.000 inches							
0.000							
Connection Style:							
•							
Plain optional end 1st end							
End Connection Design:							
Straight 1st end							
End Fitting Component And Material:							
Socket stainless steel 1st end							
Fitting Component And Surface Treatment:							
Socket passivate 1st end							
Connection Type:							
Threaded internal pipe 1st end							
Second End Relationship With First End:							
Identical							
Burst Test Pressure:							
400.0 pounds per square inch							
First End Swivel Action Capability:							
Not included							
Layer Composition And Location:							
1st layer molded rubber, ethylene propylene err-100							
Maximum Operating Pressure:							
200.0 pounds per square inch							
Thread Size:							
0.750 inches 1st end							
Measuring Method And Length:							
79.190 inches working and 80.810 inches working							
Thread Series Designator:							
Unjf 1st end							
Shelf Life:							
N/a							

NSN 4720-01-321-2557

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0