Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-321-3684

Cross Sectional Shape:
Round
Thread Class:

3b 1st end

### **Thread Direction:**

Right-hand 1st end

# **Inside Diameter:**

0.375 inches

#### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.750 inches

Minimum Inside Bending Radius:

5.000 inches

### Connection Style:

Swivel nut flare 1st end

# End Connection Design:

Straight 1st end

### **Connection Type:**

Threaded internal tube 1st end

# **Burst Test Pressure:**

16000.0 pounds per square inch

### Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,

chloroprene

### Maximum Operating Pressure:

4000.0 pounds per square inch

# Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

#### Hydrostatic Test Pressure:

8000.0 pounds per square inch

#### Inside Surface Condition:

Smooth

#### Measuring Method And Length:

60.000 inches

### **Thread Series Designator:**

Unf 1st end

Shelf Life:

N/a

### Unit Of Measure:

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

