Nonmetallic Hose Assembly - Page 1 of 2



	-	U
View Online at https://aerobasegroup.com/nsn/4720-01-321-3685		
Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.250 inches		
Tempurature Rating:		
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response		
Outside Diameter:		
0.594 inches		
Minimum Inside Bending Radius:		
4.000 inches		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 2nd end		
Connection Type:		
Threaded internal tube 1st end		
Burst Test Pressure:		
20000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer m	olded rubber	,
chloroprene		
Maximum Operating Pressure:		
5000.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
10000.0 pounds per square inch		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
66.000 inches		
Thread Series Designator:		
Unf 1st end		
Shelf Life:		
N/a		
Unit Of Measure:		

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

