NSN 4720-01-321-3686

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-321-3686 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.594 inches **Minimum Inside Bending Radius:** 4.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 20000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber, chloroprene **Maximum Operating Pressure:** 5000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 10000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 37.000 inches **Thread Series Designator:** Unf 1st end

--

N/a

Shelf Life:

Unit Of Measure:

NSN 4720-01-321-3686

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0