Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-321-4425

Cross Sectional Sha	Je:
Round	
Thread Class:	
2a 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.250 inches	
Tempurature Rating:	
-40.0 degrees fahrenh	eit and 200.0 degrees fahrenheit single response
Outside Diameter:	
0.594 inches	
Minimum Inside Ben	Jing Radius:
4.000 inches	
Connection Style:	
Swivel nut, inverted fl	are 1st end
End Connection Des	gn:
Straight 1st end	
Connection Type:	
Threaded external tub	e 1st end
Thready Qty Per Incl	(tpi):
24 1st end	
Burst Test Pressure:	
20000.0 pounds per s	luare inch
Layer Composition A	nd Location:
1st layer braided corro	sion resistant steel wire and 2nd layer braided corrosion resistant steel wire and outer layer molded rubber,
chloroprene	
Maximum Operating	Pressure:
5000.0 pounds per sq	lare inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pre	ssure:
10000.0 pounds per s	juare inch
Inside Surface Cond	tion:
Smooth	
Measuring Method A	nd Length:
52.000 inches	
Thread Series Desig	nator:
Uns 1st end	
Shelf Life:	
N/a	

NSN 4720-01-321-4425

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0